

Metal Roof Sealant



Adheres To

- Lap Joints
- Pipe Boots
- Trim
- Copper*
- Metal Siding
- Metal Roof
- PVC
- Snow Guards
- Single-Ply
- Gutters
- Aluminum
- Stucco
- Roof Flashing
- Downspouts
- Roof Tile
- Termination Bars

Product Advantages

- Adheres to Kynar® coated metals**
- Excellent adhesion and flexibility
- VOC Compliant
- Mildew Resistant
- Application Temperature -20°F to +120°F
- Freeze thaw stable
- Service Temperature -40° F to +400° F
- Invisible to UV light
- Tack free in 10 minutes
- Completely cured in up to 2 days

White MR100	Blue White MR101	Antique White MR105	Black MR110	Light Gray MR115	Dark Bronze MR120	Lincoln Bronze MR121	Sunset Red MR3903
Charcoal Gray MR126	Chocolate Brown MR131	Medium Bronze MR134	Brown MR137	Translucent MR150	Champagne MR155	Silver MR156	Champagne Metallic MR3421
Copper MR157	Hartford Green MR168	Green MR169	Regal Blue MR171***	Brandywine MR180	Red MR182	Terracotta MR184	Weathered Zinc MR3510
Sandstone MR191	Exterior Bronze MR194	Electric Blue MR195***	Regal Red MR196***	Patina Green MR197	Sierra Tan MR3333	Almond MR3461	Pearl MR3010
Gutter Gray MR3514	Hemlock Green MR3702	Pacific Blue MR3801	Silver Metallic MR4103	Coppertone MR3201	Gunmetal Gray MR117	Stone White MR102	Slate Gray MR118

* In exposed areas only

** Kynar is a registered trademark of Arkema Inc

*** Bright Color Pricing

Metal Roof Sealant

Technical Information

Product: Novaflex
Metal Roof Sealant

Appearance: Smooth paste

Service Temperature:
-40°F to +400°F

Adhesion: Excellent to most
common building materials

Consistency: Non-sag

Gunning Extrusion: Easy to gun

Durability: +/- 35-50%
depending on color/formulation

Flexibility: Good

Water Resistance: Good
– Not to be submerged

Exterior Weathering: Excellent

Aging: Excellent

Freeze-Thaw Stable: Will not freeze

Odor: None

Skin Time:

- 40°F/40% relative humidity – 40 minutes
- 75°F/50% relative humidity – 10 minutes
- 95°F/95% relative humidity – 5 minutes

Through Time:

- 40°F/60% relative humidity – 2-3 days
- 75°F/50% relative humidity – < 24 hrs

Weight per gallon: 10.2 pounds

Solids: 97%

Novaflex[®] Metal Roof Sealant provides unbeatable adhesion to metal, coated metals, wood, masonry, PVC and most common construction materials.

Product Specs

Coverage: 1/4" bead application - 28 linear feet

Specifications: Meets or exceeds ASTM C-920, TT-S-001543A and TT-S-230C

Shelf life: Use product within 18 months from manufacturer's date. FREEZE THAW STABLE.

User Tips: Not designed for continuous submersion or use below the waterline.

Clean Up: Clean tools with toluene or mineral spirits before it dries. After setting, excess sealant must be cut or scraped away. Follow solvents vendor's precautions.

Not Recommended For

- Surface temperature below 0°F or exceeding 120°F during installation
- Surfaces continuously immersed in water
- Building materials that bleed oils, plasticizers or solvents that may affect adhesion
- Frost-laden or wet surfaces
- Completely confined joints or if the sealant is intended to be painted

Limited Warranty: Satisfaction guaranteed when handled and applied according to label instructions. Call 1-800-380-0138 for Customer Service.

CAUTION!: Avoid contact with eyes and skin. Wash hands after using.

KEEP OUT OF REACH OF CHILDREN

First Aid: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately.

WARNING: Eye and skin irritant! Do not swallow. Do not allow eye contact or prolonged skin contact.

SEEK IMMEDIATE MEDICAL ATTENTION. Additional information please refer to MSDS.

Disposal: For disposal of material follow federal, state and local regulations.

Product Information

- Description - Metal Roof Sealant
- Item Number - 02-MR0XXX0-10C1
- Size - 10.3 FL. OZ (304 mL)
- Unit Dimensions - 9" x 2" x 2"

Also available in sausage packages:

Item Number - 02-MX0XXXX-20S1

Size - 20 FL Oz

Dimensions - 12 3/4" x 2" (unit)

13 1/2" x 8 1/4" x 6" (case)

Case Pack Information

- Description - Metal Roof Sealant
- Item Number - 02-MR0XXX0-10C1
- Dimensions - 11 15/16" x 9 15/16" x 8 1/8"
- Case Weight 10 lbs. / Cases Per Pallet -120



5109 Hamilton Ave.
Cleveland, OH 44114
1-800-380-0138
www.novagardsolutions.com
Made in USA. For commercial use.

